



STORE PRESSURE

CO2 MOBILE TROLLEY EXTINGUISHER

MODEL: CO20C/CO25C/CO30C



Valve	 024311001		
Seal	 0714007	 0714013	
Frame	 1001009(20KG)	 1001010(25KG)	 1001011(30KG)
Nozzle Hose	 080100040		
Safety Pin	 020901018		
Dip Tube	 080405025(20KG)	 080405026(25KG)	 080405027(30KG)
Cylinder	 050100084(20KG)	 050100085(25KG)	 050100086(30KG)
Wheel Assembly	 2012001		

TECHNICAL SPECIFICATION

Model Number	CO20C	CO25C	CO30C
Capacity(kg)	20	25	30
Cylinder Diameter(mm)	φ 219	φ 219	φ 219
Fire Rating	233B	233B	233B
Extinguisher Weight(kg)	100	110	117
Packing Size(L×W×H)(mm)	1020×480×1120	1020×480×1220	1180×550×1240
Max Working Pressure	150bar	150bar	150bar
Test Pressure	225bar	225bar	225bar
Operation Temperature	-30℃-+55℃	-30℃-+55℃	-30℃-+55℃

* Transport Classification: Non-Flammable, Non Toxic Gass. UN No.1044 Class 2.2



FEATURES:

Suitable for Class B Fires
CE Approved Brass Valve
TPED Approved Alloy Steel Cylinder with Powder Coated
100% Leak Detected.
Production Under ISO9001 Quality System

