

STORE PRESSURE MOBILE TROLLEY FIRE EXTINGUISHERS EN1866



FEATURES:

Suitable for Class A B C Fires
CE Approved Brass Valve
CE Approved Cylinder With Phosphated Treated And Red Powder Painted.
DIN EN3 Approved Pressure Gauge
Quality Rubber Hose with High Performance Nozzles
100% Helium Leak Detected.
Production Under ISO9001 Quality System
Standard: EN1866
Stainless Steel Cylinder Available

Technical Specification

Extinguisher Type	Dry Chemical Powder Trolley					
Model Number	PD25	PD30	PD50	PD50E	PD75E	PD100E
Capacity (Kg)	25	30	50	50	75	100
Cylinder Diameter(mm)	Φ 300	Φ 300	Φ 300	Φ 300	Φ 360	Φ 407
Discharge Time(s)	30	35	45	45	55	65
Fire Rating	A IIB C	A IIB C	A IVB C	A IIB C	A IVB C	A IVB C
Extinguisher Weight(kg)	58	63	91	91	128	160
Packing Size (L × W × H)(mm)2pcs	475 × 430 × 965	475 × 430 × 965	515 × 430 × 100	515 × 430 × 1100	600 × 500 × 1150	1200 × 600 × 1500
Working Pressure	15bar					
Test Pressure	30bar					
Operation Temperature	-30°C~+60°C					