

STORE PRESSURE MOBILE TROLLEY EXTINGUISHER MODEL: PD50/PD50E



Valve	 024308001		
Pressure Gauge	 040122		
Cylinder	 050100014		
Nozzle Hose	 070300015	 0806012	 080121006
Frame	 1001005		
Seal	 0714002		
Safety Pin	 020901018		
Dip Tube	 080401120		
Wheel Assembly	 2012001		

TECHNICAL SPECIFICATION

Model Number	PD50E	PD50
Capacity(kg)	50	50
Cylinder Diameter(mm)	Φ 300	Φ 300
Fire Rating	A IIIB	A IVB
Approval Number	SP162/10	SP163/10
Extinguisher Weight(kg)	90.88	90.88
Packing Size(L×W×H)(mm)	515×430×1100	515×430×1100
Working Pressure	15bar	15bar
Test Pressure	30bar	30bar
Operation Temperature	-30℃ ~+ 60℃	-30℃ ~+ 60℃

* Transport Classification: Non-Flammable, Non-Toxic Gas.
UN No.1044 Class 2.2

FEATURES:

Suitable For Class A B C Fires
CE Approved Brass Valve
CE Approved Cylinder With Phosphated And Powder Coated.
High Performance Dry Chemical Powder According to DIN EN615
100% Helium Leak Detected.
Production Under ISO9001 Quality System
CE, DIN EN1866, GS, MED, BSI Approved



CE DIN EN1866

