

STORE PRESSURE AUTOMATIC EXTINGUISHER CE



- FEATURES:
- Suitable for Class ABC Fires, (FM200 for Data & Electrical Room)
 - Automatic Sprinkler Valve (Different Temperature Bulb Available) with Pressure Release.
 - CE Approved Cylinder With Phosphated Treated and Red Powder Painted.
 - High Performance Dry Chemical Powder According to DIN EN615
- 100% Helium Leak Detected.
- Production Under ISO9001 Quality System

Technical Specification

Extinguisher Type	POWDER							FM200	
Model Number	AT-PD1	AT-PD4	AT-PD6-1	AT-PD6-2	AT-PD9	AT-PD12	AT-FM3	AT-FM6	AT-FM9
Capacity (Kg)	1	4	6	6	9	12	3	6	9
Cylinder Diamater(mm)	085	0240	0240	0280	0300	0360	240	240	300
Cylinder Height(mm)	271	164	224	180	220	220	164	224	220
Cylinder Volume(l)	1.29	5	7.20	7.50	10.50	15.80	5	7.20	10.50
Cylinder Weight(kg)	1.10	2.29	2.88	3.60	5.40	6.30	2.29	2.88	2.29
Extinguisher Weight(kg)	2.30	6.52	9.10	9.80	14.6	18.5	6.52	9.10	14.60
Packing Size (LXWXH)(mm)	385 X 280 X 375 (12PCS)	245 X 245 X 310	245 X 245 X 370	285 X 285 X 220	305 X 305 X 280	365 X 365 X 280	245 X 245 X 310	245 X 245 X 370	305 X 305 X 280
Working Pressure			15bar					25bar	
Test Pressure			30bar					30bar	
Operation Temperature			-30℃~+60℃					+5℃~+50℃	