

ABC DRY CHEMICAL HEAVY DUTY WHEELED EXTINGUISHER



FEATURES:



- Suitable for Class A B C Fires
- Squeeze Grip Aluminum Discharge Valve (PD50LB)
- Chromed/Brass Swivel Discharge Valve (PD125LB)
- Quick Opening Chromed/Brass Cylinder Valve with Gauge Guard
- Large Chromed/Brass Cap for easy filling (PD125LB)
- 3/4" Bore EPDM Hose
- DOT/TC Approved Cylinders (DOT-4BW240)
- Balanced Cylinders for Easy Transportation
- Fast Flow for Maximum Knockdown
- Integral Lifting Hoops
- 100% Helium Leak Tested
- High Performance Grade Multipurpose Dry Chemical
- Production Under ISO9001 Quality System
- 6 Year Warranty

TECHNICAL SPECIFICATION

Model Number	PD50LB	PD125LB
Capacity / lb (kg)	50(22.7)	125(56.7)
Cylinder Diameter / in/(mm)	9(229)	14(355)
Height / in (mm) approx.	45.67(1160)	51.6(1310)
Width / in/(mm) approx.	21.26(540)	27.6(700)
Depth / in (mm) approx.	27.56(700)	39.37(1000)
Discharge time / s approx.	35	39
Rate of flow / lb. per s (/kg per s)	1.5(0.68)	3.15(1.43)
Fire Rating (Tested to UL711)	20-A:120-B:C	30-A:120-B:C
Extinguisher Weight / lb.(/kg)	144.2(65.41)	284.73(129.15)
Packing Size (L×W×H) / in (mm)	/	/
Working Pressure / psi (/bar)	240(16.55)	240(16.55)
Discharge Range / ft/(m)	25-35(7.62-10.67)	25-35(7.62-10.67)
Temperature / °F (°C)	-40 to +120(-40 to +49)	-40 to +120(-40 to +49)
Hose length / ft (m)	25(7.62)	50(15.24)
Hose bore diameter / in (mm)	0.75(19)	0.75(19)
Wheels (semi-pneu.) / in (mm)	12.5(317.5)	16(406)
UL List File Number	EX 26837	EX 26837
USCG Approval Number	162.028/ EX 26837	/

* Transport Classification: Non-Flammable,Non-Toxic Gas. UN No.1044 Class 2.2