



VICTORY FIRE
NINGBO ZHENGXIN FIRE-FIGHTING EQUIPMENT CO.,LTD.



DINEN3 ISO9001

<http://www.zxfire.net>

STORE PRESSURE

6KG DRY CHEMICAL POWDER FIRE EXTINGUISHER

MODEL: PD6/PD6E

3Pcs & Deep Drawn Cylinder Available



Valve	 024304008	 024304013	 024304004	 024304003
Pressure Gauge	 040107	 040320		
Seal	 0714002			
Nozzle Hose	 070307001	 080100003		
Bracket	 070200001	 070201005	 070202004	
Safety Pin	 020901017			
Dip Tube	 080401025			
Cylinder	 050103011	 050100013		
Hose Catch	 071001			
Plastic Base	 0704005			

TECHNICAL SPECIFICATION

Model Number	PD6	PD6E
Capacity(Kg)	6	6
Cylinder Diameter(mm)	φ 150	φ 150
Fire Rating	55A 233B C	34A 183B C
Approval Number	SP 113/09	SP 27/09
Extinguisher Weight(kg)	9.56	9.56
Packing Size(L×W×H)(mm)	165×165×540	165×165×540
Working Pressure	14bar	14bar
Test Pressure	30bar	30bar
Operation Temperature	- 30℃- + 60℃	- 30℃- + 60℃

* Transport Classification: Non-Flammable, Non Toxic Gass.
UN No.1044 Class 2.2

FEATURES:

Suitable For Class A B C Fires
CE Approved Brass Valve
CE Approved Cylinder With Phosphated treated And Powder Coated.
High Performance Dry Chemical Powder According to DIN EN615
100% Helium leak Detected.
Production Under ISO9001 Quality System
CE, DIN EN3, GS, MED, BSI Approved



DINEN3

