



VICTORY FIRE
NINGBO ZHENGXIN FIRE-FIGHTING EQUIPMENT CO.,LTD.



TÜV Rheinland®
Precisely Right.

DIN EN1866 ISO9001

<http://www.zxfire.net>

STORE PRESSURE CO2 MOBILE TROLLEY EXTINGUISHER MODEL: CO20C



Valve	 024315001	
Cylinder	 (219mm) 050100267	 (232mm) 050100285
Nozzle Hose	 080100088	 080100089
Shield	 2012069	
Frame	 1000002	
Seals	 0714002	 0714006
Safety Pin	 020901010	
Dip Tube	 080402059	
Wheel Assembly	 2012001	

TECHNICAL SPECIFICATION

Model Number	CO20C
Capacity (Kg)	20
Cylinder Diameter (mm)	Ø 219 / Ø 232
Fire Rating	144B
Approval Number	SP 60/18
Extinguisher Weight (kg)	82
Packing Size (L×W×H) (mm)	790×630×1180
Max Working Pressure	169.3bar
Test Pressure	250bar
Operation Temperature	-20℃~+60℃

* Transport Classification: Non-Flammable, Non Toxic Gass.
UN No.1044 Class 2.2

FEATURES:



Suitable for Class B Fires
TPED Approved Brass Valve
TPED Approved Alloy Steel Cylinder
with Powder Coated
100% Leak Detected.
Production Under ISO9001 Quality System
T, DIN EN1866, GS, MED, BSI Approved



DIN EN1866

