

STORE PRESSURE MOBILE TROLLEY EXTINGUISHER MODEL: FM50/FM50-C



Valve	 024308002	
Pressure Gauge	 040130	
Cylinder	SUS304L  50100070	 50100162
Nozzle Hose	 0806011	 080100057
Frame	 1001008	
Seal	 0714002	
Safety Pin	 020901018	
Dip Tube	 080405007	
Wheel Assembly	 2012001	

TECHNICAL SPECIFICATION

Model Number	FM50	FM50-C
Capacity(L)	50	
Cylinder Diameter(mm)	Ø 300	
Discharge Time(s)	45	
Fire Rating	A IVB	
Approval Number	SP 04/15	
Extinguisher Weight(kg)	90.88	
Packing Size(L×W×H)(mm)	515×430×1100	
Working Pressure	12bar	
Test Pressure	30bar	
Operation Temperature	+5℃ -+60℃	

* Transport Classification: Non-Flammable, Non Toxic Gass.
UN No. 1044 Class 2.2

FEATURES:



Suitable For Class A B Fires
CE Approved Brass Valve
CE Approved stainless steel Cylinder And Powder Coated.
High Efficiency AFFF Foam
100% Helium leak Detected.
Production Under ISO9001 Quality System
CE, DIN EN1866 ,GS , MED, BSI Approved

