



VICTORY FIRE
NINGBO ZHENGXIN FIRE-FIGHTING EQUIPMENT CO.,LTD.



DINEN3 ISO9001

<http://www.zxfire.net>

STORE PRESSURE MOBILE TROLLEY EXTINGUISHER MODEL: PD50/PD50E



Valve		024308001				
Pressure Gauge		040122				
Cylinder		050100014				
Nozzle Hose		070300015		0806012		080121006
Frame		1001005				
Seal		0714002				
Safety Pin		020901018				
Dip Tube		080401120				
Wheel Assembly		2012001				

TECHNICAL SPECIFICATION

Model Number	PD50E	PD50
Capacity(kg)	50	50
Cylinder Diameter(mm)	Φ 300	Φ 300
Fire Rating	A IIIB	A IVB
Approval Number	SP162/10	SP163/10
Extinguisher Weight(kg)	90.88	90.88
Packing Size(L×W×H)(mm)	515×430×1100	515×430×1100
Working Pressure	15bar	15bar
Test Pressure	30bar	30bar
Operation Temperature	-30℃ ~+ 60℃	-30℃ ~+ 60℃

* Transport Classification: Non-Flammable, Non-Toxic Gas.
UN No.1044 Class 2.2

FEATURES:

Suitable For Class A B C Fires
CE Approved Brass Valve
CE Approved Cylinder With Phosphated And Powder Coated.
High Performance Dry Chemical Powder According to DIN EN615
100% Helium leak Detected.
Production Under ISO9001 Quality System
CE, DIN EN1866, GS, MED, BSI Approved



DIN EN1866

