



VICTORY FIRE & GAS INC.

www.victoryfiregas.com
info@victoryfiregas.com

Michigan Corporate Office
1713 Lewis St
Bay City MI 48706
989.322 0856

Texas
15550 West Hardy
Houston TX 77060
281 405 0175

Illinois
162 N. Brandon Dr.
Glendale Heights IL 60139
312 965 2697

Northern CA
2214 American Ave
Hayward CA 94545
510 861 5311

Pennsylvania
30 Three Tun Rd, Unit C
Malvern PA 19335
267 963 6411

Southern CA
14841 Proctor Ave Unit C
City of Industry CA 91746
626.333 3033

Florida
5182 Le Tourneau Circle
Tampa FL 33610
813 999 4424

Georgia
3968 Shirley Drive
Atlanta GA 30336
770 283 4780

CANADA BC
104-1772 Broadway St.
Port Coquitlam, BC V3C2M8
778-222-6765

CANADA Toronto ON
1104 Fewster Drive Unit 12 & 13
Mississauga ON L4W2V7
416-898-6390

CARBON DIOXIDE

FEATURES:

Suitable for Class B and C Fires
Plated Brass Valve with
Stainless Steel Handles
Aluminum Cylinder
100% Leak Tested
Production Under ISO9001 Quality System



TECHNICAL SPECIFICATION

Model Number	CO5LB	CO10LB	CO15LB	CO20LB
Capacity(lb/kg)	5(2.27)	10(4.54)	15(6.8)	20(9.07)
Cylinder Diameter(in/mm)	5.24(133)	6.89(175)		8(203)
Height(in/mm)	17.13(435)	29.92(760)	35.82(910)	36.02(915)
Width(in/mm)	8.07(205)	11.42(290)		12.40(315)
Discharge Time(s)	9	10	14	18
Fire Rating	2-B:C	10-B:C		10-B:C
Extinguisher Weight(lb/kg)	13.29(6.03)	26.7(12.11)	36.04(16.35)	47.97(21.76)
Packing Size(L×W×H)(in/mm)	7.67×5.7×17.72(195×145×450)	11.62×7.28×20.08(295×185×510)	11.62×7.28×26.77(295×185×680)	12.8×8.44×27.17(325×215×690)
Discharge Range(ft/m)	4-8(1.2-2.4)	4-8(1.2-2.4)		4-8(1.2-2.4)
Operation Temperature(F/C)	-22~120(-30~49)	-22~120(-30~49)		-22~120(-30~49)
UL list File Number	EX 27916	EX 27916		EX 27916
Marine Type	/	B:C Size I	B:C Size II	/
USCG Approval Number	/	162.028 EX 27916		/

* Transport Classification: Non-Flammable, Non-Toxic Gas. UN No. 1044 Class 2.2