

ABC Dry Chemical

ABC Dry Chemical is a multipurpose extinguishing agent that is suitable for use on Class A, Class B and Class C fires.

Typical Uses: For public areas such as offices, classrooms, churches, parking garages, and hotel/motel assembly halls and guest areas. For businesses such as retail stores, light manufacturing facilities, research facilities, auto dealerships, vehicle/ aircraft/marine service centers, and manufacturing processes such as painting, dipping, and coating.

Not recommended for use on sensitive electronic equipment or aircraft structure.

Third Party Approvals For Peace Of Mind



Model	2.55A-ABC	5HISA40-ABC 5HISB40-ABC*	5HISA40-ABC 5HISB40-ABC*	10HI SA80 ABC 10HI SB80 ABC*	10SHISA-ABC	20SHISA-ABC 20SHISB-ABC*	30SHISB-ABC*
Description	2.5 lb. ABC Vehicle Bracket	5 lb. ABC Wall Mount	5 lb. ABC Vehicle Bracket	10 lb. ABC Wall Mount	10 lb. Short ABC Wall Mount	20 lb. ABC Wall Mount	30 lb. ABC Wall Mount
Pt. # Alum. Valve	13315	10914	25614	11340	11310	12120	N/A
Pt. # Brass Valve	N/A	10915	25615	11341	N/A	12121	12905
Agent Capacity	2.5 lb. (1.13 kg)	5 lb. (2.27 kg)	5 lb. (2.27 kg)	10 lb. (4.54 kg)	10 lb. (4.54 kg)	20 lb. (9.07 kg)	30 lb. (13.6 kg)
UL/ULC Rating	1-A:10-B:C	3-A:40-B:C	3-A:40-B:C	4-A:80-B:C	4-A:60-B:C	10-A:120-B:C	10-A:160-B:C
Temperature Range	-65° to 120°F (-54° to 49°C)						
Discharge Time	9 sec	14 sec	14 sec	22 sec	18 sec	27 sec	32 sec
Discharge Range ft (m)	9-15 (2.7-4.6)	12-18 (3.7-5.5)	12-18 (3.7-5.5)	15-21 (4.6-6.4)	15-21 (4.6-6.4)	15-21 (4.6-6.4)	25-30 (7.6-9.1)
Operating Pressure	100 psi (689 kPa)	195 psi (1344 kPa)	195 psi (1344 kPa)	195 psi (1344 kPa)	195 psi (1344 kPa)	195 psi (1344 kPa)	195 psi (1344 kPa)
USCG Approval	Type B:C Size I	Type A Size II Type B:C Size I	Type A Size II Type B:C Size I	Type A Size II Type B:C Size II	Type A Size II Type B:C Size II	Type A Size II Type B:C Size III	Type A Size II Type B:C Size IV
Ship Weight**	5.5 lb. (2.5 kg)	10 lb. (4.5 kg)	10.25 lb. (4.7 kg)	18.25 lb. (8.3 kg)	18.75 lb. (8.6 kg)	33.5 lb. (15.2 kg)	52.25 lb. (23.7 kg)
Unit Height	14.75 in (37.5 cm)	16.375 in (41.6 cm)	16.375 in (41.6 cm)	21 in (53.3 cm)	16.75 in (42.5 cm)	21.25 in (53.8 cm)	27.375 in (69.4 cm)
Unit Width	4.875 in (12.4 cm)	7.25 in (18.4 cm)	7.25 in (18.4 cm)	7.75 in (19.7 cm)	8.25 in (21 cm)	8.75 in (22.2 cm)	8.75 in (22.2 cm)
Unit Diameter	3.375 in (8.6 cm)	4.25 in (10.8 cm)	4.25 in (10.8 cm)	5.125 in (13 cm)	6 in (15.2 cm)	7.5 in (19.1 cm)	7.5 in (19.1 cm)