

Wet Chemical - Class K

Our Wet Chemical extinguishers contain a blend of Potassium Acetate and Potassium Citrate that is extremely effective in suppressing high temperature fires involving cooking oils and grease.

The units incorporate a spray nozzle that ensures the agent is applied gently to the burning oil thus preventing splashing. It’s unique cooling properties deliver exceptional heat absorption ensuring the fire remains out.

Wet Chemical is suitable for use on Class A and K fires.

Typical Uses: For protecting cooking oil and grease fires in commercial kitchens. This extinguisher is designed to complement existing pre-engineered hood systems.



Model	WC-6L	WC-2.5
Description	6 Liter Wet Chemical	2.5 Gallon Wet Chemical
Part #	50006	50025
Cylinder/Valve Material	Stainless Steel/Plated Brass	Stainless Steel/Plated Brass
UL/ULC Rating	1-A:K	1-A:K
Temperature Range	40° to 120° (4.4° to 49°C)	40° to 120° (4.4° to 49°C)
Discharge Time	54 secs.	74 secs.
Mounting Type	Wall	Wall
Operating Pressure	100 psi (690 kPa)	100 psi (690 kPa)
Ship Weight	22.75 lb. (10.3 kg)	30 lb. (13.6 kg)
Unit Height	19.25 in (48.9 cm)	24.5 in (62.2 cm)
Unit Width (incl. hose)	9 in (22.9 cm)	9 in (22.9 cm)
Cylinder Diameter	7 in (17.8 cm)	7 in (17.8 cm)



Used in conjunction with Kitchen Mister
Fire Suppression System.
Page 24 – 26.

Third Party Approvals For Peace Of Mind

