



WATER MIST

• MR CONDITIONAL

This extinguisher has been demonstrated to pose no known hazards in an MRI environment of 7-Tesla or less.

- Contains de-ionized water providing protection in "clean room", telecommunication, and hospital-type facilities.

FEATURES:

Suitable for Class A and C Fires
Brass Valve Stainless Steel Handle
Stainless Steel Cylinder
100% Helium Leak Tested
Production Under ISO9001
Quality System



TECHNICAL SPECIFICATION

Model Number	WM2.5GAL	WM6L
Capacity / gal(L)	2.5(9.46)	1.6(6)
Cylinder Diameter / in(mm)	7.07(179.5)	7.07(179.5)
Height / in(mm)	27.76(705)	24.6(625)
Width / in(mm)	9.65(245)	9.65(245)
Discharge Time / s	78	40
Fire Rating	2-A:C	2-A:C
Extinguisher Weight / lb(kg)	28.66(13.00)	20.68(9.38)
Packing Size(L×W×H) / in(mm)	7.48×7.48×28.35(190×190×720)	7.48×7.48×25.19(190×190×640)
Working Pressure / psi(bar)	100(6.9)	100(6.9)
Discharge Range / ft(m)	10-12(3-3.6)	10-12(3-3.6)
Operation Temperature / F(°C)	40~120(4~49)	40~120(4~49)
UL list File Number	EX 28801	EX 28801
USCG Approval Number	/	/

* Transport Classification: Non-Flammable, Non-Toxic Gas. UN No.1044 Class 2.2